

AUTOMATION AND OPTIMIZATION LABRATORY

Path Planning with Power Schedules for Solar-Powered Ground Robot

Optimization Method, Types of Path Plans, Test Environment Setup and Evaluation, and Future Work


Nathaniel Kingry, Kishan Patel and Ran Dai

IOWA STATE UNIVERSITY

AEROSPACE
ENGINEERING 


OBJECTIVE

Minimize the travel time of a solar-powered, unmanned, ground vehicle through an area with no net energy loss




MODIFIED PARTICLE SWARM OPTIMIZATION

- Non-uniform solar radiation distributions
- Particle Swarm Optimization (PSO) creates a number of candidate solutions or particles
 - It is an iterative process
 - After each iteration, the particles are evaluated and compared to each particle's best recorded parameters and the group's best.
 - Each particle is comprised of the vehicle's waypoint locations, linear velocities, and rotational velocities at each turn.
- Constraints of the Problem
 - Negligible Net Energy Loss over path
 - Minimize Travel Time



Graphical Representation




Example Motion Plan

TYPES OF PATH PLANS

Balkcom-Mason


- Governed by three differential – drive primitives
 - Forward, clockwise, and counterclockwise rotation



Example of Balkin-Mason Path Planning

Pseudo-Dubin


- Derived from Dubin Curves
- Characterized by variable turn radius and continuous differential drive
 - Allows for forward and circular arc turns




Example of Pseudo-Dubin Path Planning

SOLAR ENERGY MAP EXAMPLE


The solar energy density produced by a single light is sampled and generated into a scalar field.



SOLAR ENERGY MAP EXAMPLE



0:00.000




IOWA STATE UNIVERSITY

AEROSPACE
ENGINEERING




BALKCOM-MASON MOTION PLAN EXAMPLE

A three light environment is navigated with negligible net energy change using a Balkcom-Mason motion plan produced from our modified heuristic optimizer.



BALKCOM-MASON MOTION PLAN EXAMPLE




IOWA STATE UNIVERSITY


AEROSPACE
ENGINEERING



BALKCOM-MASON MOTION PLAN EXAMPLE



00.000




IOWA STATE UNIVERSITY

AEROSPACE
ENGINEERING





PSEUDO-DUBIN MOTION PLAN EXAMPLE

The three light environment is now navigated with negligible net energy change using the previous waypoints and a Pseudo-Dubin motion plan.



PSEUDO-DUBIN MOTION PLAN EXAMPLE




IOWA STATE UNIVERSITY


AEROSPACE
ENGINEERING



PSEUDO-DUBIN MOTION PLAN EXAMPLE



00.000



— Estimated P_{IN} — Estimated P_{OUT} — Predicted Battery Energy Change
● Experimental P_{IN} ● Experimental P_{OUT} ● Experimental Battery Energy Change

IOWA STATE UNIVERSITY

AEROSPACE
ENGINEERING




MOTION PLAN RESULTS

Balkcom-Mason Motion PLAN

Time: 25.22 s


Final Battery Energy: -0.56 J



Pseudo-Dubin Motion PLAN

Time: 20.12 s

Final Battery Energy: +3.67 J






TIME REDUCTION: **20.22%**

IOWA STATE UNIVERSITY

AEROSPACE
ENGINEERING



FUTURE WORK: VISUAL LIGHT DENISTY MAPPING



Benefits:

- Have knowledge of an area before entering
- Faster and more efficient than current point-based data gathering approach
- Allows for snap-shots of Time-Variant areas.

